

KLAUSNER PRODUCTS

Klausner Products	Standard Sizes in mm (unless otherwise indicated)	Species	Grade/Class
Structural Timber S4S, EE, KD	1 x 4/6/8 inches (19x89/140/184 mm) 2 x 2/4/6/8/10 inches (38x38/89/140/184/235 mm)	Spruce Pine	CLS/SLS and J-Grade # 2 & com. and # 3 & com.
Construction Timber rough sawn Sizes KD 18 +/- 2 %	22/25 x 100/125/150/175/195/215/225/235/245/295 32/38 x 100/125/150/175/195/215/225/235/245/295 45 x 100/125/150/175/195/215/225/235/245/295 50 x 100/125/150/175/195/215/225/235/245/295 63 x 100/125/150/175/195/215/225/235/245/295 75 x 100/125/150/175/195/215/225/235/245/295 95 x 100/125/150/175/195/215/225/235/245/295	Spruce	Sawfalling including s/e Vls
Packaging Timber rough sawn Sizes KD 18 +/- 2 %	22 x 95/100/125/145/150/175/195/225/245 25 x 100/125/145/150/175/195/225/245	Spruce Pine	Sawfalling including s/e Vls
Squares rough sawn Sizes KD 18 +/- 2 %	70 x 70/72 x 72/75 x 75 90 x 90/92 x 92/95 x 95 72 x 95/72 x 145/72 x 200 75 x 95/75 x 145/75 x 200	Spruce Pine	Sawfalling including s/e Vls
Pine / Red Wood rough sawn Sizes KD 18 +/- 2 %	25 x 100/125/150/175/195/225/245 38 x 100/200/225/245 50 x 200/225/245 63 x 100/200	Pine	Sawfalling including s/e Vls
Low grade Green and KD	Various thicknesses Various widths	Spruce Pine	Low / reject grade

Notes: General lengths range: 3,00 to 5,00 m. Other sizes available on request.


 KLAUSNER
 20140007
 DRY
 EW/ER SS C24
 KLAUSNER